

PolyFoam™

BaseGrade Underlayment



A D V A N T A G E S

PolyFoam™ polyethylene foam underlayment offers protection for all brands of applicable flooring. This padding provides a cost efficient source of underlayment for wooden substructures. Our foam underlayment products utilize the latest technology to assure protection while meeting specifications.

PolyFoam™ is manufactured for the flooring industry with the highest quality cell structure while maintaining specified densities. PolyFoam™ underlayment is produced with low corrugation and is available in standard or customized dimensions.

P R O D U C T S P E C I F I C A T I O N S

Foam Density	1.4# (+/- 15%)
Foam Thickness	.080
Compression Set	<15% of original thickness
Roll Size	48" Wide (100 Sq.Ft & 200 Sq.Ft)
Roll Weight	Approximately 2.1# (+/-15%)
Foam Thickness & Color	White
R Value	3 per inch

100 sq. ft. Roll Packaging:

1 pallet = 81rolls

1 truck load = 52 pallets (4,212 rolls)



I N S T A L L A T I O N I N S T R U C T I O N S

- Always read the flooring manufacturers recommendations and instructions before installing the underlayment.
- Before rolling out the underlayment, be sure to sweep, vacuum, and remove all debris on the substructure.
- Fill in any significant holes, gaps or breaks that may exist on the substructure.
- Roll out the Underlayment over the substructure surface.
- Splice each roll of underlayment with a 3mm film tape, duct tape, or similar pressure-sensitive tape that meets/exceeds the water vapor transmission ratings suggested by the flooring manufacturer.
- Always be sure to connect the rolls together evenly so that the foam is not overlapping each other and there are no wide gaps between the foam.

